



# SUBMITTAL INFORMATION

METER SETTER  
6040NL-2\_\_H4H4-VV



3/4" REDUCED PORT METER BALL VALVE BY REDUCED PORT METER BALL VALVE  
CB COMPRESSION x CB COMPRESSION FOR COPPER OR PLASTIC TUBING (CTS)



## METER SETTER CATALOG NUMBERS

HEIGHT	CATALOG NUMBER	APPROX. WT. LBS.
9"	6040NL-209H4H4-VV	
12"	6040NL-212H4H4-VV	

- FEATURES:
- MANUFACTURED IN COMPLIANCE WITH AWWA STANDARD C800 (ASTM B-584 UNS NO C89833 FOR BRASS PARTS IN CONTACT WITH POTABLE WATER, AND ASTM B-62 AND B-584 UNS NO C83600 FOR ALL OTHER BRASS PARTS).
  - CONFORMS TO ANSI/NSF 61-8
  - CONFORMS TO ANSI/NSF 372 (COMPLIANT WITH US Safe Drinking Water Act. PL 111-380)
  - METER SWIVEL SADDLE NUTS HOLD THE METER IN PLACE FOR TIGHTENING.
  - TIE BAR IS STANDARD FOR 18" AND TALLER METER SETTER HEIGHTS.
  - 13/16" OD COPPER TUBE RISERS.
  - ASSEMBLED WITH LEAD-FREE SOLDER.
  - VERTICAL BRACING EYE IS STANDARD.
  - CONSTRUCTED WITH TYPE K COPPER TUBING, ALLLOY C12000 MANUFACTURED TO ASTM B88.
  - EPDM METER GASKETS PROVIDED
  - ANGLE VALVE HAS PADLOCK WINGS FOR LOCKING VALVE IN CLOSED POSITION.
  - 180 DEG. FAHRENHEIT MAXIMUM CONSTANT TEMPERATURE.
  - 300 PSI MAXIMUM WORKING PRESSURE.

Cambridge Brass considers the information in this submittal form to be correct at the time of publication. Item and option availability, including specifications, are subject to change without notice.

Cambridge Brass  
P.O. Box 249, 140 Orion Place  
Cambridge, Ontario  
Canada N1R 5V1  
Tel: (519) 621-5520  
Fax: (519) 621-8674  
<http://www.cambridgebrass.com>



SUBMITTED BY: